



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/665,346	09/22/2003	Yujin Yamazaki	826.1895	7037
21171 7590 03/15/2007 STAAS & HALSEY LLP SUITE 700			EXAMINER	
			CHANG, AUDREY Y	
1201 NEW YORK AVENUE, N.W. WASHINGTON, DC 20005			ART UNIT	PAPER NUMBER
			2872	
SHORTENED STATUTOR	Y PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE	
3 MONTHS		03/15/2007	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

	Application No.	Applicant(s)					
	10/665,346	YAMAZAKI ET AL.					
Office Action Summary	Examiner	Art Unit					
	Audrey Y. Chang	2872					
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address					
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).							
Status							
1) Responsive to communication(s) filed on 05 Ja	nuary 2007.						
,	·						
•	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is						
closed in accordance with the practice under E	closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims							
4)⊠ Claim(s) <u>1-5 and 7-24</u> is/are pending in the application.							
4a) Of the above claim(s) is/are withdrawn from consideration.							
5) Claim(s) is/are allowed.							
6)⊠ Claim(s) <u>1-5 and 7-24</u> is/are rejected.							
7) Claim(s) is/are objected to.	· · · · · · · · · · · · · · · · · · ·						
8) Claim(s) are subject to restriction and/or election requirement.							
Application Papers							
9) The specification is objected to by the Examine	r.						
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.							
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).							
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).							
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.							
Priority under 35 U.S.C. § 119							
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received.							
 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). 							
* See the attached detailed Office action for a list of the certified copies not received.							
Attachment(s)	_						
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Di 5) Notice of Informal F 6) Other:	ate					

Art Unit: 2872

DETAILED ACTION

Page 2

Continued Examination Under 37 CFR 1.114

- 1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on **January 5, 2007** has been entered.
- 2. This Office Action is also in response to applicant's amendment filed on **January 5, 2007**, which has been entered into the file.
- 3. By this amendment, the applicant has amended claims 1, 5, 10-11, 14, 15, and has newly added claims 16-24.
- 4. Claims 1-5, and 7-24 remain pending in this application.
- 5. The rejections of claims 1, 14 and 15 under 35 USC 112, first paragraph, with regard to newly added matters set forth in the previous Office Action are withdrawn in response to applicant's amendment.

Response to Amendment

6. The amendment filed January 5, 2007 is objected to under 35 U.S.C. 132(a) because it introduces new matter into the disclosure. 35 U.S.C. 132(a) states that no amendment shall introduce new matter into the disclosure of the invention. The added material which is not supported by the original disclosure is as follows: the amended claims 1, 14-17 and newly added claims 22 and 24 recite the phrase "fixing material does not block the light from entering the substrate through light input portion". The specification simply fails to disclose such explicitly. The newly submitted claims 22 and 24 further recite the phrase "the fixing material is fixed to first side of VIPA" and the phrase "means for

Page 3

Art Unit: 2872

fixing the fixing material to the first side of the VIPA" respectively, and these claims also recites that the "VIPA" comprises only a substrate. This means the fixing material is fixed to the substrate, which is not supported by the specification. The newly added claim 24 also recites the phrase "means for fixing the fixing material" wherein the specification fails to disclose what is the means for fixing the fixing material.

Applicant is required to cancel the new matter in the reply to this Office Action.

Claim Rejections - 35 USC § 112

7. The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

8. Claims 1-5 and 7-24 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.

The reasons for rejection based on the newly added materials are set forth in the paragraphs above.

9. Claims 22-24 are rejected under 35 U.S.C. 112, first paragraph, as based on a disclosure which is not enabling. A first and a second reflective films formed on first and second side of the substrate respective are critical or essential to the practice of the invention, but not included in the claim(s) is not enabled by the disclosure. See *In re Mayhew*, 527 F.2d 1229, 188 USPQ 356 (CCPA 1976). Claims 22 and 24 recite a virtually-imaged phased array (VIPA) but it comprises only a substrate. The specification and the claims fail to teach how could a substrate be capable of forming a virtually-imaged phase array.

Art Unit: 2872

10. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

11. Claims 1-5 and 7-24 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claims 1, 14, 15, 22 and 24 recite a virtually-imaged phase array (VIPA) comprising a substrate, and a fixing material, however it is not clear how does this fixing material logically relate to the substrate (with first reflective and second reflective films) and the fixing material as to definite defined the function of the "optical device". In particular, the fixing material does not seem to have any optical function which makes it confusing as how does it contribute to optical function in relating to the substrate or the virtually-imaged phase array. This fixing material is therefore interpreted as any kind of adhesive or support means that can hold or support the VIPA.

Claim Rejections - 35 USC § 102

12. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

13. Claims 22-24 are rejected under 35 U.S.C. 102(b) as being anticipated by the patent issued to Okumura et al (PN. 5,969,902).

Okumura et al teaches a disk substrate serves as the apparatus that is comprised of a disk substrate (12, Figure 5), serves as the substrate having first and second sides opposite to each other and a

Art Unit: 2872

support member (such as spacers 20, shims 30 and clamps 40), served as the fixing material, fixed to the first surface of the disk substrate, that is made of material having approximately the same thermal expansion coefficient as the substrate, (please see column 10, lines 54-69). Okumura et al teaches that the disk substrate can be made of glass material which is transparent to light which therefore defines portion for the light to enter the substrate and the fixing material is placed at the position that does not block the light from entering the disk substrate (please see Figure 5).

Although this reference does not teach explicitly that the disk substrate is a "virtually-imaged phase array (VIPA)", however it has been held that a recitation with respect to the *manner* in which a claimed apparatus is intended to be employed does not differentiate the claimed apparatus from a prior art apparatus satisfying the claimed structural limitations. Ex parte Madham, 2 USPQ2d 1647 (1987).

It is implicitly true that there is means, such as hands or machine, for fixing the support members or fixing material to the first surface of the disk substrate.

This reference has therefore anticipated the claims.

Claim Rejections - 35 USC § 103

- 14. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 15. Claims 1, 5, 7-15 and newly added claims 16-17 are rejected under 35 U.S.C. 103(a) as being unpatentable over the patent issued to Shirasaki (PN. 5,930,045) in view of the patents issued to Spiller et al (PN. 6,134,049), and Okumura et al (PN. 5,969,902).

Shirasaki teaches a virtual imaged phased array (VIPA) that is comprised of a substrate (164, Figures 12(A) or 240 in Figure 13) and a first reflecting film (166 or 242) placed on a first surface of the

Art Unit: 2872

substrate and a second reflecting film (168 or 244) placed on a second surface of the substrate. The two reflecting films each comprises at least one layer and implicitly has a first and second refractive index. Shirasaki further teaches the first reflecting film (166 or 242) is placed on a first surface of the substrate and the second reflecting film (168 or 244) placed on a second surface of the substrate, and the first and second surface of the substrate are opposite to each other. As shown in Figure 13, Shirasaki et al teaches that the substrate has a light input portion on the first surface of the substrate.

Page 6

This reference has met all the limitations of the claims. However it does not teach explicitly that the first and second reflecting films of multi-layer film structure with plural films. It also does not teach explicitly that the VIPA has a stress correction film formed on the second multi-layer film. It is a rather standard knowledge in the art to make the reflective film with multi-layer structure comprising alternatively laminated high and low refractive index materials, as explicitly demonstrated by the teachings of Spiller et al wherein the reflecting layer has multi-layer structure of alternatively arranged high and low refractive index materials, (please see Figure 1). Such modification would then have been obvious to one skilled in the art for the benefit of using the multi-layer structure to design reflective layers having desired reflection characteristics by varying the structure of the multi-layer films. Spiller et al in the same field of endeavor further teaches to compensate or reduce stress of a multi-layer film by placing on top the multi-layer film a film (13, Figure 1) having a stress value that would balance the stress value of the multi-layer film (12) so that a net stress may assume value zero, (please see Figures 1 and 2). It would then have been obvious to apply the teachings of Spiller et al to add a stress correction layer on top of the multi-layer film of the VIPA for the benefit of reducing the possible damages or distortion to the substrate of the VIPA induced by the stress of the reflecting films and by the expansion of the substrate under high heat environment. Although these references do not teach explicitly that the stress correction film is provided to correct the stress imposed by both reflecting films on the both sides of the substrate, such feature is implicitly included since for the VIPA having the pair of reflecting films, the

distortion due to the thermal effect in the environment.

Art Unit: 2872

stress is contributed from both reflecting films and the stress value of the correction film must be selected to compensate the net stress value contributed from both reflecting films.

With regard to the feature concerning the substrate is fixed to a fixing layer having the same

thermal expansion coefficient as the substrate, it is not clear what is the logical relationship between the fixing material and the substrate and the optical device it therefore can only be examined in the broadest interpretation. It is implicitly true that the VIPA of Shirasaki must be held by a holder in order for it to be positioned and utilized in an optical system such as shown in Figures 13 and 17-19. This means the VIPA is fixed with certain fixing material such as a holder. It is well known in the art that in a high temperature environment, materials of different thermal expansion coefficient will expand or contract differently, which may cause distortion to the device. It would then have been obvious to one skilled in the art to make the holder of the VIPA having the same thermal expansion coefficient as the substrate of VIPA, as explicitly taught by Okumura et al to make the disk substrate support member and the disk substrate with the materials having the same thermal expansion coefficient, (column 10, lines 59-68) to prevent distortion to the substrate when held by the support member or the holder for the benefit of eliminating distortion and errors in the substrate and therefore the VIPA filter. With regard to the feature that the fixing material is fixed to the first surface of the substrate, Okumura et al teaches an example of the holder and the disk substrate wherein the holder (20, 30 or 40, Figure 5) is fixed at first surface of the substrate. With regard to the feature concerning the fixing material not blocking the light from entering the substrate, (as recited in claims 1, 14, 15, 16 and 17), Okumura et al teaches such arrangement explicitly also, (please see Figure 5). It would then have been obvious to one skilled in the art to apply the teachings of Okumura et al to provide a holder for the VIPA device of Shirasaki et al for the benefit of fastening and supporting the VIPA device in place and without causing

Art Unit: 2872

With regard to claim 5, Shirasaki teaches that the VIPA (240, Figures 17-20) may be utilized with a mirror (254) to realize a dispersion compensator.

With regard to claims 7-13, Okumura et al teaches that the fixing material or support member may be made of materials such as ceramics or glass, (please see column 10, lines 59-67). Although these references do not teach that the holder or the fixing material is made of the other various materials as claimed, such modifications would have been obvious to one skilled in the art to select desired materials having the same thermal expansion coefficient as the holder for the VIPA for the benefit of using a variety of alternative materials as the materials for making the holder that fixes the substrate of the VIPA and at the same time not cause distortion to the substrate. The fixing to the protector plate may be considered as optically jointed.

16. Claims 1-4 are rejected under 35 U.S.C. 103(a) as being unpatentable over the patents issued to Shirasaki (PN. 5,930,045) in view of the patents issued to Fujii et al (PN. 5,424,876) and Okumura et al (PN. 5,969,902).

Shirasaki teaches a virtual imaged phased array (VIPA) that is comprised of a substrate (164, Figures 12(A) or 240 in Figure 13) and a first reflecting film (166 or 242) placed on a first surface of the substrate and a second reflecting film (168 or 244) placed on a second surface of the substrate. The two reflecting films each comprises at least one layer and implicitly has a first and second refractive index.

Shirasaki further teaches the first reflecting film (166 or 242) is placed on a first surface of the substrate and the second reflecting film (168 or 244) placed on a second surface of the substrate, and the first and second surface of the substrate are opposite to each other. As shown in Figure 13, Shirasaki et al teaches that the substrate has a light input portion on the first surface of the substrate.

This reference has met all the limitations of the claims with the exception that it does not teach explicitly that the first and second reflecting films of multi-layer film structure with plural films.

Art Unit: 2872

However it is a rather standard knowledge in the art that reflective film can be formed by multi-layer structure with plural layers of different refractive index materials. Fujii in the same field of endeavor teaches a reflective film that is comprised of plural layers of different refractive index. It would then have been obvious to one skilled in the art to modify the reflective layer of Shirasaki et al with plural layers of different refractive index materials for the benefit of using the multi-layer structure to design reflective layers having desired reflection characteristics.

Furthermore, this reference does not teach explicitly that the VIPA has a stress correction film formed on the second multi-layer film. Fujii in the same field of endeavor teaches to use a silicon dioxide layer in a multi-layer mirror such that the silicon dioxide layer imposes a compressive stress on the substrate of the multi-layer mirror such that the stress on the substrate resulted from all the other multi-layer films in the mirror may be reduced, (please see column 2, lines 1-49). It would then have been obvious to apply the teachings of Fujii to add a silicon dioxide layer to the VIPA as a stress correction layer for the benefit of reducing the possible damages or distortion to the substrate of the VIPA induced by the stress of the reflecting films and by the expansion of the substrate under high heat environment. Although these references do not teach explicitly that the stress correction film (i.e. the silicon dioxide film) is provided to correct the stress imposed by both reflecting films on the both sides of the substrate. Such modification would have been obvious to one skilled in the art since the thickness of the silicon dioxide as Fujii teaches explicitly (please see column 4, lines 3-8), is selected particularly to correct and compensate the net stress upon the substrate whether the stress is from one film on one side or films on the both sides. The stress on the substrate is a resultant net stress on the substrate and that resultant stress is being corrected by the silicon dioxide layer with selected thickness. With regard to claims 2-4, Fujii teaches that the stress correction film is a silicon dioxide film and its thickness may be adjusted to properly reduce the stress. The thickness of the silicon dioxide film is also selected so that it does not affect the optical property of the multi-layer mirror. It is a well-known knowledge in the art that

Art Unit: 2872

in a multi-layer film structure, in order for the layer not to effect the optical property the layer should have an optical thickness of half or multiple of half of the specific wavelength of interested in order for the light effected by the layer be completely out of phase. Such modification therefore is considered obvious to one skilled in the art so that the silicon dioxide layer will not affect the reflectivity of the reflective layers (166 or 168). The optical flatness of the substrate being within one wavelength or less is rather standard in the art for the purpose of reducing unwanted scattering of the light at the surface.

Although this reference does not teach explicitly that the stress correction layer is placed on the multi-layer film, however since the net stress of the reflecting mirror is the vector sum of the stress contributed by the reflecting multi-layer and the correction film, to place the stress correction film either on the multi-layer film or under does not effect the purpose of reducing the stress. Such modification would then have been obvious to one skilled in the art for the benefit of designing the reflecting mirror as desired and to fit the particular application requirements.

With regard to the feature concerning the substrate being fixed to a fixing layer having the same thermal expansion coefficient as the substrate, it is not clear what is logical relationship between the fixing material and the substrate and the optical device it therefore can only be examined in the broadest interpretation. It is implicitly true that the VIPA of Shirasaki must be held by a holder in order for it to be positioned and utilized in an optical system such as shown in Figures 13 and 17-19. This means the VIPA is *fixed* to certain *fixing material* such as a *holder*. It is well known in the art that in a high temperature environment, materials of different thermal expansion coefficient will expand or contract differently, which may cause distortion. It would then have been obvious to one skilled in the art to make the holder of the VIPA having the same thermal expansion coefficient as the substrate of VIPA, as explicitly taught by **Okumura** et al to make the disk substrate *support member* and the disk *substrate* with the materials having the *same* thermal expansion coefficient, to prevent distortion to the substrate when held by the support member or the holder for the benefit of eliminating distortion and errors in the

Art Unit: 2872

substrate and therefore the VIPA filter. Okumura et al teaches that the support member is placed at a position of the disk substrate that does not block the entering of the light into the substrate.

17. Claims 18, and 20-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over the patent issued to Shirasaki (PN. 5,930,045) in view of the patent issued to Okumura et al (PN. 5,969,902).

Shirasaki teaches a virtual imaged phased array (VIPA) that is comprised of a substrate (164, Figures 12(A) or 240 in Figure 13) and a first reflecting film (166 or 242) placed on a first surface of the substrate and a second reflecting film (168 or 244) placed on a second surface of the substrate. The two reflecting films each comprises at least one layer and implicitly has a first and second refractive index.

Shirasaki further teaches the first reflecting film (166 or 242) is placed on a first surface of the substrate and the second reflecting film (168 or 244) placed on a second surface of the substrate, and the first and second surface of the substrate are opposite to each other. As shown in Figure 13, Shirasaki et al teaches that the substrate has a light input portion on the first surface of the substrate that allows light to enter the substrate and being reflected between the first and second reflective films.

This reference has met all the limitations of the claims with the exception it does not teach explicitly to have a fixing material. However it is really not clear what is the logical relationship between the fixing material and the substrate and the optical device it therefore can only be examined in the broadest interpretation. It is implicitly true that the VIPA of Shirasaki must be held by a holder in order for it to be positioned and utilized in an optical system such as shown in Figures 13 and 17-19. This means the VIPA is *fixed* with certain *fixing material* such as a *holder*. It is well known in the art that in a high temperature environment, materials of different thermal expansion coefficient will expand or contract differently, which may cause distortion to the device. It would then have been obvious to one skilled in the art to make the holder of the VIPA having the same thermal expansion coefficient as the

substrate of VIPA, as explicitly taught by **Okumura** et al to make the disk substrate support member and the disk substrate with the materials having the same thermal expansion coefficient, (column 10, lines 59-68) to prevent distortion to the substrate when held by the support member or the holder for the benefit of eliminating distortion and errors in the substrate and therefore the VIPA filter.

With regard to the feature that the fixing material is fixed to the first surface of the substrate, Okumura et al teaches an example of the holder and the disk substrate wherein the holder (20, 30 or 40, Figure 5) is fixed at first surface of the substrate. With regard to the feature concerning the fixing material not blocking the light from entering the substrate, (as recited in claims 18, 20 and 21), Okumura et al teaches such arrangement explicitly also, (please see Figure 5). It would then have been obvious to one skilled in the art to apply the teachings of Okumura et al to provide a holder for the VIPA device of Shirasaki for the benefit of fastening and supporting the VIPA device in place and without causing distortion due to the thermal effect in the environment.

18. Claim 19 is rejected under 35 U.S.C. 103(a) as being unpatentable over the patents issued to Shirasaki and Okumura et al as applied to claim 18 above, and further in view of the patent issued to Spiller et al (PN. 6,134,049).

The VIPA optical device taught by Shirasaki in combination with the teachings of Okumura et al as described for claim 18 above have met all the limitations of the claim.

This reference however does not teach explicitly that the VIPA has a stress correction film formed on the second multi-layer film. Spiller et al in the same field of endeavor teaches to compensate or reduce stress of a multi-layer film by placing on top the multi-layer film a film (13, Figure 1) having a stress value that would balance the stress value of the multi-layer film (12) so that a net stress may assume value zero, (please see Figures 1 and 2). It would then have been obvious to apply the teachings of Spiller et al to add a stress correction layer on top of the multi-layer film of the VIPA for the benefit of

Application/Control Number: 10/665,346 Page 13

Art Unit: 2872

reducing the possible damages or distortion to the substrate of the VIPA induced by the stress of the reflecting films and by the expansion of the substrate under high heat environment. Although these references do not teach explicitly that the stress correction film is provided to correct the stress imposed by both reflecting films on the both sides of the substrate, such feature is implicitly included since for the VIPA having the pair of reflecting films, the stress is contributed from both reflecting films and the stress value of the correction film must be selected to compensate the net stress value contributed from both reflecting films. Furthermore, one skilled in the art would understand that to place the stress correction layer on the first or the second reflective layer of Shirasaki would function the same in reducing the stress in the layer structure, since the correction layer is designed to correct the net stress introduced by all the layers.

Response to Arguments

- 19. Applicant's arguments filed January 5, 2007 have been fully considered but they are not persuasive. The newly amended claims have been fully addressed in the paragraphs above.
- 20. Applicant's arguments are mainly drawn to the newly amended features and newly added claims that they have been fully addressed in the paragraphs above.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Audrey Y. Chang whose telephone number is 571-272-2309. The examiner can normally be reached on Monday-Friday (8:00-4:30), alternative Mondays off.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Stephone B. Allen can be reached on 571-272-2434. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Page 14

Application/Control Number: 10/665,346

Art Unit: 2872

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Audrey Y. Chang, Ph.D. Primary Examiner

Art Unit 2872

A. Chang, Ph.D.